

Suzuki Jimny 2005 on - Centre Console Trim Removal by Halford

Just had to remove the centre console trim to fix an annoying rattle

(additionally wanted to know how to do it in readiness for eventually swapping the CD/Radio combo for a single DIN CD/mp3 player and CB fitment and also junking the cigarette lighter to fit a stand-alone aux power socket with new wiring)

Firstly pull the ashtray out

and remove the cigarette lighter



Next disconnect the power supply to the lighter socket – ref point 1 on the image



The power supply simply "pulls-off"



Next, undo the x3 screws holding the ashtray guide and remove



Now, put your hands under the lower trim facia and use your fingers to gently lift the xxx at ref points 2 and 3 whilst at the same time easing the lower trim towards you.

Once these clips are free, simply work your way up the panel gently lifting the facia until it's free all the way up.



The facia trim should now be free, but you'll need to disconnect the Hazard Button before you can pull it away.

Simply nip the sides of the block and gently pull it out.



Now we have the trim removed

There are x6 clips (ref points 5 to 10) that need to be removed as they must be fitted to rear of the trim before refitting.

The easiest way to remove them is to turn them sideways then carefully extract.



Here we have the rear of the trim panel with the clips attached, ready for refitting.

These are the clips

I Believe the part ref is:
A-pillar: 09409-06324

